

JST-SMR-03V-B

1

2

3

Pin1 -- 棕色/+

Pin2 -- 空 /NC

Pin3 -- 蓝色/-

Technical drawing of the C-FQH2-200X150-X LED strip light. The drawing includes three main views: a front view, a side view, and a detail view of the mounting bracket (局部C). The front view shows a rectangular light strip with a central circular opening of diameter 40mm. The overall width is 155mm, and the height is 80mm. The side view shows the light strip's profile with a width of 18mm and a height of 198mm (for two-sided side installation). The detail view (局部C) shows the mounting bracket with dimensions 4.7mm, 2.5mm, 1.2mm, 8.5mm, 5.5mm, and 3.3mm. The drawing also includes a cross-section A-A (剖面 A-A) showing the internal structure of the light strip, with dimensions 164mm, 150mm (lighting surface), 214mm, 200mm (lighting surface), 10.5mm, and 300mm. The text '局部C' (Detail C) is used to identify the mounting bracket detail.

局部C
四面, M3螺母, 安装用
比例: 2: 1

注: 产品频闪要求: 亮20ms\灭80ms.

产品安装尺寸图					设计			wordop®沃德普		
输入电压	理论电耗功率				审核					
	红色 (R)	白/蓝/绿色 (WGB)	红外 (IR)	紫外 (UV)	估重	视角方向	比例	单位	名称	底部开孔背光源
24V		45W					1:1	mm	型号	C-FQH2-200X150-X