



规格	参数	尺寸		额定功率	估重 (kg)
		A	B		
C-TLN-280W-FN-X		280	300	260	5.3
C-TLN-380W-FN-X		380	400	380	6.6
C-TLN-480W-FN-X		480	500	400	8.0
C-TLN-580W-FN-X		580	600	500	9.4
C-TLN-680W-FN-X		680	700	580	10.8
C-TLN-780W-FN-X		780	800	2X330	12.2
C-TLN-880W-FN-X		880	900	2X375	13.6
C-TLN-980W-FN-X		980	1000	2X410	15.0
C-TLN-1080W-FN-X		1080	1100	2X450	16.4
C-TLN-1180W-FN-X		1180	1200	2X500	17.8
C-TLN-1280W-FN-X		1280	1300	2X530	19.2
C-TLN-1380W-FN-X		1380	1400	2X570	20.6
C-TLN-1480W-FN-X		1480	1500	4X305	22.0
C-TLN-1580W-FN-X		1580	1600	4X325	23.4

产品安装尺寸图					备注	设计					wordop 沃德普
输入电压	理论电耗功率				1. 建议匹配延长线: FCB-LN3系列延长线	审核					
	红色 (R)	白/蓝/绿色 (WGB)	红外 (IR)	紫外 (UV)		公差标准	IT14				
48V					2. 建议匹配控制器: PSC4系列控制器	估重	视角方向	比例	单位	名称	C-TLN-X系列
							1:1	mm	型号		